

WaveWare Wall Pager AS-110 Series

10 Character LED Sign



"We Deliver Information at the Speed of Light"

10 Characters with 4" Tall Fonts*

*** Also Available in 20 Characters**

Features:

- Alpha LED display, red display color
- 10 characters per line, right to left scrolling for messages longer than 10 characters
- Messages are received wirelessly from wide area or on-site paging systems
- No special message formatting required. Displays exactly what is sent to your pagers
- Messages are automatically managed for up to 24 active messages
- Message timeout option using either time or message display count as timeout triggers
- Display memory of 163K Bytes, and accepts up to 2,000 characters per message
- 4.0" characters can be read at a distance of up to 200 feet
- Real Time Clock, with message time-stamping option
- Mounting bracket kit included
- Over-the-air programmable operating configuration
- Message clearing feature using "reset" key-string
- Programmable default message of up to 50 characters, appears when all dynamic messages clear
- Source ID feature allowing message headers to identify message Cap Code, e.g. "Code Blue: "
- Message annunciation interface via on-board relay, selectable by Cap Code (factory upgrade)

Specifications:

- **Model:**
AS110 Alpha Sign, WaveWare Wall Pager Configuration
- **Frequency:**
138~174MHz, 408~473MHz, 929~932MHz, factory configuration
- **RF Data Rate:**
512 / 1200 / 2400bps for POCSAG
- **Channel Spacing:**
25KHz
- **Code Format:**
POCSAG (VHF, UHF, or 900 band), or FLEX (900 band only)
- **Cap Codes:**
6 Cap Codes for POCSAG
- **LED Array:**
160 x 16
- **Characters:**
10/4.00" tall
- **Dimensions:**
Case: 28 (L) x 6(H) x 3(D) in.
- **Weight:**
Approximately 8.5 lb.
- **Power:**
110VAC, 6 ft. power cord included