

# WaveWare 2-Line Wall Pager Model AS-122R



*"We Deliver Information at the Speed of Light"*

**2-Lines with 2" Tall Fonts or 1-Line with 4" Tall Fonts\***

**\* Also Available in 10 Characters**

## Features:

- Alpha LED Display, Red Display Color
- Sign Operates in Single Mode, 1-Line or 2-Line, Specify Mode when Ordering
- One Line Mode: 20 Characters per line, Right to Left Scrolling for Messages Longer than 20 Characters.
- Two Line Mode: 26 Characters per line with Page Flipping for Messages Longer than 52 Characters
- Messages are Received Wirelessly from Wide-Area or On-Site Paging Systems, Wireless Receiver Included
- No Special Message Formatting required. Displays Exactly what is Sent to your Pagers
- Messages are Automatically Managed for up to 24 Active Messages
- Message Time-Out Option using either Run Time or Message Display Count as Time-Out Triggers
- Priority Message Stacking for up to 5 Priority Messages
- Priority Message by Prefix (911)
- Mail Drop by Cap Code, Mail Drop Time-Out, to Support News Feeds
- 4.0" Characters can be read at a Distance of up to 200 feet
- 2.0" Characters can be read at a Distance of up to 100 feet
- Real Time Clock, with Message Time-Stamping Option
- Over-the-Air Programmable Operating Configuration
- Message Clearing Feature using "reset" by Prefix/Suffix
- Delete All Messages via Over-the-Air Command
- Programmable Default Message of up to 50 Characters, Appears when all Dynamic Messages Clear
- Source ID Feature Allowing Message Headers to Identify Message Cap Code, e.g. "Code Blue: " Specify Msg Headers when Ordering
- Message Annunciation Interface via On-Board Relay, Selectable by Cap Code or with Priority Message (Relay Option Built-In)
- Optional Horn and Strobe Kit for Annunciation of New Messages

## Specifications:

- **Model:**  
AS-122R Alpha Sign, WaveWare Wallpager Configuration
- **Frequency:**  
138~174MHz, 408~473MHz,  
929~932MHz, factory configuration
- **RF Data Rate:**  
512 / 1200 / 2400bps for POCSAG
- **Channel Spacing:**  
25KHz
- **Code Format:**  
POCSAG (VHF, UHF, or 900 band), or  
FLEX (900 band only)
- **Cap Codes:**  
6 Cap Codes for POCSAG
- **LED Array:**  
320 x 16
- **Characters:**  
20/4.00" tall (One-Line Mode)  
52/2.00" tall (Two-Line Mode)
- **Dimensions:**  
Case: 51 (L) x 6(H) x 3(D) in.
- **Weight:**  
Approximately 15.3 lb.
- **Power:**  
110VAC, 6 ft. power cord included

- Relay Output Activation by Cap Code or Priority Message
- Mounting Bracket kit Included