

Apollo 812 Alphanumeric Pager



“Your Source for Pagers”



Key Specifications/Special Features:

- Synthesized or Crystal Type
- True Mini-Pocket Size
- Two Line
- User Friendly Interface
- Selective PC or Hand Programmable
- Support Languages: English, Spanish, Portuguese, Russian, and French

Specifications:

Model:
AL-812

Frequency:
138~174MHz, 279~282 MHz, 443~473MHz,
929~932MHz

Paging Sensitivity:
512bps - 5 μ V/M, 1200bps - 7 μ V/M, 2400bps -
9 μ V/M

Bit Rate:
512 / 1200 / 2400bps for POCSAG

Channel Spacing:
25KHz

Code Format:
POCSAG

Spurious Rejection:
40db below carrier

Alert Tone Loudness:
85db @ 30 cm (12 inches)

Cap Codes:
6 Cap Codes

View Area:
40 x 12.70 mm

Dimension:
61(L) x 42(W) x 18(H) mm

Weight:
Approximately 35 g (Without Battery)

Features:

- 36 Alphanumeric or 7 Chinese character One page Display
- Selective PC or Hand Programmable
- Total Capacity:
13312 Alphanumeric or 6656 Chinese characters
- General Message:
10 sets + full message
Receives messages of up to 2000 Alphanumeric or 1000 Chinese characters
- Total General Memory Capacity:
3000 Alphanumeric or 1500 Chinese characters
- Personal Message:
10 sets
Total Personal Memory Capacity:
1000 Alphanumeric or 500 Chinese characters
- Mail Drop:
25 sets
Total Mail Drop Memory Capacity:
9216 Alphanumeric or 4608 Chinese characters
- Time and Date Display:
American Date Format: mm-dd-yy
British Date Format: dd-mm-yy
- 10 sets of memory, six lockable
- 4 Alert Modes:
Beeper, Vibrator, Melody, Sleep
- 10 Melody Alerts, 4 Beeper Sounds
- Group Call function can set per individual code
- LCD Backlight for easy viewing
- Indicates the current time with one alarm function
- Low Voltage indicator and alarm