

Apollo **GOLD XP** Alphanumeric Pager



"Your Source for Pagers"



Specifications:

Model:
VP-200

Frequency:
39-43MHz, 84-88MHz, 143-147MHz and 406-512MHz

Paging Sensitivity:
4 μ V/M

Selectivity:
60 dB

Spurious Image Rejection:
55 dB

Audio Output @ 12:
95/93 dBa (Audio/Voice)

Frequency Stability:
10 PPM

Voice Level:
93 dba @ 12

Frequency Deviation:
+/- 4.5 KHz

Code Format:
31/21 POCSAG (CCIR Code #1)

Dimension:
80(L) x 53(W) x 20(H) mm

Weight:
Approx. 56g (without Battery)

Features:

- Synthesized
- **IP-54 Specification** Protection from Rain or Dust
- Single or Dual Channel Option
- Wide Band and Narrow Band Capable
- 8 Minutes of Stored Voice Memory
- 4 Position Selector Knobs
- Function Mode Announcement
- Priority Scan, Normal Scan and Silent Scan Functions
- Programmable Tone and Vibrate Alerts
- User Programmable Tones for Different Addresses
- Channel Monitor Function
- Low Battery Alert
- Earphone Jack
- Standard Desktop Charger Base, **Included**
- **Optional** Amplified Charger Base