

Apollo XL-2000 Numeric Pager



“Your Source for Pagers”



Key Specifications/Special Features:

- Synthesized or Crystal Type
- Top Read Display
- Slide Switch, Select Beep or Vibe or Off
- Loud Buzzer / Strong Vibration
- Uses AA Battery

Dimension:

51(L) x 74(W) x 28(H) mm

Weight:

Approximately 76 g (Without Battery)

Battery:

One 1.5 V AA Alkaline Battery

Specifications:

Model:

AL-A01 (XL-2000)

Frequency:

138~174MHz, 408~473MHz, 929~932MHz

Paging Sensitivity:

512bps - 5 μ V/M, 1200bps - 7 μ V/M,
2400bps - 9 μ V/M

Bit Rate:

512 / 1200 / 2400bps for POCSAG, 1600 / 3200 /
6400bps for FLEX

Channel Spacing:

12.5KHz, 25KHz

Selectivity:

60db @ 25KHz

Code Format:

POCSAG, FLEX

Spurious Rejection:

40db below carrier

Alert Tone Loudness:

85db @ 10 cm

Cap Codes:

4 Cap Codes for POCSAG, 16 Cap Codes for FLEX

Display:

12 Digits

Frequency Deviation:

\pm 4.5 KHz

Features:

- 40 Alphanumeric Canned Messages
- 10 Programmable Canned Messages
- Back-Light display
- Selective PC or hand Programming
- 16 Memory Slots
- Slide Switch, Select Beep or Vibrate Alert
- Message Full Indicator
- Memory Retention
- Message Lock
- Extra Long Battery Life
- Real Time Clock Calendar
- 9 Caller ID Activated Beep Tone
- Direct Show (Option)
- Message Invert (Option)
- Duplicate Message
- Low Battery Indicator
- Message Time Stamping
- Date, and Time Display
- Selective Erase All
- Lithium Battery Backup
- Reminder Alert
- Up to 4 Cap Codes capability, 16 Cap Codes Capability for Flex
- Alerts with LED Flash