

MaxPage Multi-Function Paging System



Specifications:

- **Recipient Capacity:**

9999 Pagers (Tone, Numeric, Alphanumeric or Coaster Pagers)

- **Group Capacity:**

20 Groups (with any combination of recipients / groups)

- **Manual Paging Methods:**

Via built-in keypad, optional P/S-2 keyboard or optional windows software

- **Reminder Messages:**

10 Reminder messages can be configured for booked calls

- **Function Keys:**

4 x dual mode function keys for preconfigured messages

- **Alarm Capacity:**

4 alarm inputs (Dry contact closure type with common ground)

- **Alarm Programming:**

32 character, alphanumeric message

Programmable activation delay

Call escalation with programmable escalation time periods

- **PBX Interface: (ADD-ON Option)**

RJ-11, two wire Analogue Extension (voice prompted)

- **PBX Messages:**

10 x User defined messages

Note: Programming can be done thru the keypad or by using the PC Software (provided), but paging thru the serial port is an "ADD-ON" Option.

- **2-Tone Voice Paging (ADD-ON Option)**

- **Internal Transmitter:**

2 or 5 watts

- **Frequencies:**

VHF: 138-170 MHz, UHF: 450-470 MHz

- **Supported Paging Protocols:**

POCSAG @ 512, 1200, and 2400 bps

- **Serial Port Protocols: (ADD-ON Option)**

Scope, TAP and Comp 1 & Comp 2

- **Included Keypad:**

19 numerical backlit silicon keys

- **External Keyboard: (ADD-ON Option)**

Any P/S-2 compatible keyboard

- **LCD:**

2-Line x 16 character backlit LCD

- **Power Requirements:**

12-13.8 volt VDC at 2 A regulated

- **Dimensions:**

360 x 220 x 86 mm (14 x 8.7 x 3.4 inches)

- **Weight:**

2.5kg / 5.5 lbs.