

PT- 5000- KW

19" Rack Mounted HIGH Power Paging Terminal



Specifications:

- **Paging Encoding:**
WaveWare SPS-5 v7 Encoder Board, built-in.
- **Transmitter:**
Kenwood Land Mobile Radio, Model TK-760G (H) VHF or Model TK-860G (H) UHF.
- **Band Width:**
Narrow Band (12.5 kHz) or Wide Band (25 kHz).
- **Paging Protocols:**
POCSAG Alphanumeric, Numeric, Tone/Vibe at RF Data rates of 512, 1200 and 2400 bps Auto-switching.
- **Interface Protocols:**
TAP, Comp 1 & Comp 2, and WaveWare Proprietary Interface, via DIP switch selection.
- **Frequency Programming:**
Frequency(s) are factory programmed and can be set up with multiple channels and with different power levels.
- **Power Supply:**
Model SEC-1223-R1
13.8 VDC output
120 VAC input
Rated at 23 Amps
- **RF Power Out:**
5-50 watts VHF or 5-40 watts UHF.
- **Pager Database:** 5,994 Maximum, EEPROM
Programmed with Windows based programming software, (included with system).
- **Compatible with:**
WaveWare Enterprise Messaging Software
WaveWare Alert Pro Software
Rauland Borg Responder Nurse Call Systems
Emergin Wireless Office
And many others.
- **Dimensions:**
19" W x 15" D x 9" H
- **Cooling Fan,** built-in.

NOTES:

Also available with other paging encoder models.
Requires an External Antenna.

WaveWare Technologies, Inc.

www.wirelessmessaging.com

1-800-373-1466