

PageLynx Standard Paging System



PageLynx Standard is basically identical to the PageLynx Pro, but **without** the Keyboard and LCD.

Windows Access:

The PC software provided with the PageLynx Std allows the user to program and send messages. The Windows software may also be used for dial in access.

PBX Interface:

A voice prompted telephone interface enables staff to send messages directly to pagers without the assistance of an operator. The user is guided through the paging process via voice prompts.

Alarm Monitoring:

PageLynx Std is supplied with 16 alarm inputs with the ability to expand this through the use of AIM modules. As soon as an alarm is triggered a predefined message describing the alarm, its location as well as any details concerning the alarm will be instantly sent to the appropriate personnel.

Free Text /High Level Interface:

In addition to supporting alarm inputs PageLynx Std provides a "free text" interface enabling keywords to be scanned for within a serial data stream. Once the keyword is located PageLynx Std may dispatch the message to local or wide area pagers.

Wide Area Paging:

The modem enables PageLynx Std to call wide area paging companies to send messages.

Technical Specifications:

- **Transmitter:**
External 2 or 5 watts
- **Recipient capacity:**
500 recipients
- **Group capacity:**
20 Groups
- **Alarm capacity:**
208 Alarm inputs
- **On board alarms:**
16 contact closure inputs
- **Free Text Interface:**
10 keywords
- **PBX Interface:**
2 Wire Analogue Extension
- **PBX Messages:**
10 x User defined messages
- **Paging protocols:**
POCSAG at 512/1200bps
TAP, TNPP, Kirk DECT
- **Input protocols:**
"Free Text" interface
- **Carrier capacity:**
10 x Carriers (TAP/SMS)
- **Serial Ports:**
2 x RS232 Serial Ports
- **Power requirements:**
12V DC at 500mA
- **Email Integration:**
POP3 Client over TCP/IP
- **Dimensions:**
14 x 8.7 x 3.4 inches
Weight 2.5kg /5.5lb