

NOVA NP-30 Numeric Synthesized Pager (like the LS-355)



Features:

- Synthesized
- Vibration, Tone, Melody and Silent Alert
- 6 Individual Addresses
- Memory Capacity: 16 Messages, total 320 digits
- Message Full Indicator
- Message Time Stamping
- Delete All/One Message
- Memory Backup (when replacing battery)

- Out of Range Indicator
- Low Battery Alert & Indicator

Display:

- Large Display
- Backlight
- Date and Time Display

Specifications:

Protocol	POCSAG
UHF Frequency MHz	450 - 470 MHz
VHF Frequency MHz	143 - 174 MHz
Frequency Stability	0.0045% from 41°F to 104°F
Channel Spacing	25 KHz
Sensitivity / Alerting	5.0uV/m@512 bps
Transmission Speed	512 / 1200 / 2400 bps
Adjacent Channel Selectivity	55dB @ +/-25KHz
Modulation	+/-4.5KHz
Intermediate Frequency	21.4MHz/455KHz
Spurious Rejection	> 40 dB
Image Rejection	> 40 dB
Intermodulation Rejection	> 50 dB
Alert Response	>75db @ 30cm
Operating Temperature	14°F to 104°F
Battery Type	1 AA Alkaline
Dimensions	2.7"(L) X 2.0"(W) X 0.7"(H)