

Apollo 812 Alphanumeric Pager



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com



P/N= 812ES - 469 for UHF (450- 470 MHz)
P/N= 812ES - 100 for VHF (150-170 MHz)

Key Features:

- Synthesized
- True Mini-Pocket Size
- Double Back-Light LCD Display
- 2-Line Display Pager
- Zoom from 2-Line to 1-Line
- Quick Scroll in 1-Line Mode
- User Friendly Interface
- Program by PC Software or by Hand thru the Buttons
- Supported Languages: English, Spanish, Portuguese, Russian, German and French.

Specifications:

- Model: AL-812
- Frequency: 408-473 MHz, 138-174 MHz and 929-931 MHz
- Paging Sensitivity: 512bps - 5 μ V/M, 1200bps - 7 μ V/M, 2400bps - 9 μ V/M
- Pager Baud Rate: 512 / 1200 / 2400bps for POCSAG
- Channel Spacing: 25KHz Wide Band (WB)
- Code Format: POCSAG (6 Cap Codes)
- Spurious Rejection: 40db below carrier
- Alert Tone Loudness: 85db @ 10 cm
- View Area: 45 x 14.43mm
- Dimension: 61(L) x 42(W) x 18(H) mm

Features:

- 2-Line Display
- Total of 36 Characters on Display for POCSAG
- 26 Memory Slots
- 4 Beeps Alerts, 8 Melody Alerts, Vibration and Sleep mode
- Message Full Indicator
- 1 Daily Alarm Set
- Mail Drop (Unlimited Characters per Mail Drop)
- 10 Extra Personal Slots (POCSAG)
- Spring Loaded Holster
- Sequential Lockout Option
- Time and Date Display
- Selective Message Lock / Delete
- Lithium Battery Backup
- Variety of Case Colors (See Color Chart Below)

NOTE: Frequency Required when Ordered

