

Apollo Coaster Pager



“Your Source for Pagers”



Key Specifications/Features:

- Synthesized or Crystal Type
- Tone / Vibrate / Flash only Pager
- For Guest Paging / Compact Size
- PC Programmable
- Recommended use with Desktop Transmitter TE- 310 / TE-250N / WaveWare TouchCall or other Numeric Paging Systems
- **Requires** Charger Base (Sold Separately)
- Tone, Vibrate and Flash (13 LED) Alert
- Over the air “Off”
- 4 Addresses (with 4 functions per address)
- Programmable Alert Type
- Two LED (Heartbeat, Alert, Out of Range and Low Battery)
- Ni-MH Rechargeable Battery

Specifications:

Model:

AL- 205

Frequency:

138- 174MHz, 408- 473MHz

Paging Sensitivity:

512bps---5uV/M, 1200bps---7uV/V, 2400bps---9uV/M

Bit Rate:

512 / 1200 / 2400bps for POCSAG

Channel Spacing:

25KHz

Code Format:

POCSAG

Spurious Rejection:

40db Below Carrier

Alert Tone Loudness:

85db @ 10 cm

Cap Codes:

4 Cap Codes for POCSAG

Dimension:

109.08 Diameter x 15.9 mm (H)

Weight (with Battery):

Approximately: 115g

WaveWare Technologies Inc. **1-800-373-1466** www.wirelessmessaging.com

Coaster Pager

Charger Base



"Your Source for Pagers"



Key Specifications / Features:

- The charger allows you to place the coasters on the stack and to charge coasters through charging pins.
- Each charger has two jacks for cascading multiple chargers together using the jumper wire included.
- One charger base and 5v/800mA power adapter – charges up to 15 coasters.
- Two charger bases, 1 jumper wire and 5v/800mA power adapter- charges up to 30 coasters.
- Dimension: 109.08mm (Diameter) x 15.19 mm (H)
- Weight: Approximately: 75 g