

Apollo T-2000 Numeric Pager



“Your Source for Pagers”



Key Specifications/Special Features:

- Synthesized or Crystal Type
- Top Side Read
- Classic Style
- Soft Touch
- Small Size
- Fancy Color

Dimension:

43(L) x 60(W) x 18(H) mm

Weight:

Approximately 39.5 g (Without Battery)

Battery:

One 1.5 V AAA Alkaline Battery

Specifications:

Model:

AL-901

Frequency:

138~174MHz, 408~473MHz, 929~932MHz

Paging Sensitivity:

512bps - 5 μ V/M, 1200bps - 7 μ V/M, 2400bps - 9 μ V/M

Bit Rate:

512 / 1200 / 2400bps for POCSAG, 1600 / 3200 / 6400bps for FLEX

Channel Spacing:

25Khz

Selectivity:

60db @ 25KHz

Code Format:

POCSAG (AL-901), FLEX (AF-901)

Spurious Rejection:

40db below carrier

Alert Tone Loudness:

85db @ 30 cm (12 inches)

Cap Codes:

4 Cap Codes for POCSAG, 16 Cap Codes for FLEX

Display:

12 Digits

Frequency Deviation:

\pm 4.5 KHz

Features:

- 40 Alphanumeric Canned Messages
- Back-Light display
- Selective PC or hand Programming
- 16 Memory Slots
- 4 beep Alerts, 10 Melody Alerts, Vibration-Sleep Mode
- Message Full Indicator
- 5 Daily alarm sets
- 8 Message Locks
- Extra Long Battery Life
- Real Time Clock Calendar
- 9 Caller ID Activated Beep Tone
- Extension compatibility
- 10 personal extra slots
- Duplicate Message Detection
- Unread Message Display
- Message Time Stamp
- Month, Date, Year, Time Display
- Selective Message Lock/Delete
- Lithium Battery Backup
- Reminder Alert
- Up to 4 Cap Codes capability, 16 Cap Codes Capability for Flex
- Dual Mode Pager (POCSAG & FLEX two system in one pager)