

# Apollo T-2000 Numeric Pager



*"Your Source for Pagers"*

Visit Our Website at:

[www.WirelessMessaging.com](http://www.WirelessMessaging.com)



P/N= 2000-460MHz for UHF

P/N= 2000-100MHz for VHF

## Key Features:

- Top Read Display
- Synthesized or Crystal Type
- Classic Style / Soft Touch / Small Size
- Back-Lit Display
- User Friendly Interface
- Program by PC Software or by Hand thru the Buttons

## Specifications:

- Model: AL- 901 (Also called the T-2000)
- Frequency: 408-473 MHz, 138-174 MHz and 929-932 MHz
- Paging Sensitivity: 512bps - 5 $\mu$ V/M, 1200bps - 7 $\mu$ V/M, 2400bps - 9 $\mu$ V/M
- Pager Baud Rate: 512 / 1200 / 2400bps for POCSAG, 1600 / 3200 / 6400bps for FLEX
- Channel Spacing: 25 KHz (WB) or 12.5KHz (NB)
- Code Format: POCSAG (AL-901) or Flex (AF-901)
- Selectivity: 60 db @ 25 KHz
- Spurious Rejection: 40db below carrier
- Alert Tone Loudness: 85db @ 30 cm (12 inches)
- Cap Codes: 4 Cap Codes for POCSAG, 16 Cap Codes for FLEX
- Weight: Approx. 39.5 Grams (w/o Battery)
- Dimension: 43(L) x 60(W) x 18(H) mm

## Features:

- 40 Alphanumeric Canned Messages
- 16 Memory Slots
- 4 Beeps Alerts, 10 Melody Alerts, Vibration and Sleep mode
- Message Full Indicator
- 5 Daily Alarm Sets
- 8 Message Locks
- Extra Long Battery Life
- Real Time Clock Calendar
- 9 Caller ID Activated Beep Tone
- 10 Extra Personal Slots
- Duplicate Message Detection
- Unread Message Indicator
- Message Time Stamp
- Month, Date, Year and Time Display
- Selective Message Lock / Delete
- Reminder Alert
- Lithium Battery Backup
- Variety of Case Colors (See Color Chart Below)  
New Colors: Totally Red and Solid Blue (Not Shown)

**NOTE:** Frequency Required when Ordered

