

Apollo TP-200 Desktop “Big Screen” Pager

Easy to Read Large Display - Adjustable Volume - Loud Buzzer



“Your Source for Pagers”



Features:

- Pocsag / Synthesized / Desktop.
- Up to 8 Cap Codes
- Adjustable Volume, Loud Buzzer.
- Large 4-Line Display or Zoom for 2-Line.
 - 120 x 44 mm View Area
- 6 Keys Operation with User Friendly Interface.
- Options:
 - 3 AAA - Rechargeable Battery Back Up.
 - Relay / Data Output.
- Support Languages:
 - English, Spanish, French and More.
- 6-Line, Total 84 Alphanumeric One Page Display.
- Large Memory Size: Total Capacity of 259,062 Characters.
- General Message: 16 Sets + Message Full: 10 Sets, Total Capacity of 20480 Characters.
- Personal message: 10 sets, Total Capacity of Memory 1,000 Alpha Characters.
- Mail drop: 15 sets, Total Capacity of 228,345 Alpha Characters.
- Month, Date, Year, Time Display (British Date Format dd-mm-yy or American Date Format mm-dd-yy).
- 12 or 24 Hr Format Real Time Clock (Selectable).
- Real Time Clock Calendar.
- Unread Message Reminder Alert.
- Error Message Indicator.
- Duplicate Message Indicator.
- 10 Sets for Messages Lock.
- Message Time Stamp.
- Message Full Indicator.
- Manual pager on/off.

- Message auto storage.
- Auto Scroll.
- Auto Sleep.
- Out-of-range indication (1min, 2mins, 5mins, 10mins, disabled).
- 5 sets of daily alarms.
- 4 Beep Alerts with LED Flash.
- 10 Melody Alerts with LED Flash.
- Page Scrolling, User-Selectable.
- Zoom In / Zoom Out.

Specifications:

- Model: TP-200 (Alphanumeric Pager)
- RF frequency range: 138-174Mhz, 408-472Mhz, 929-932Mhz.
- Paging sensitivity:
 - 30 dBuV/M for 512 bps POCSAG.
 - 33 dBuV/M for 1200 bps POCSAG.
- EIA Selectivity: 60 dB \pm 25KHz.
- Spurious rejection: 55 dB below carrier.
- Image rejection: 50 dB below carrier.
- Frequency Stability: -10° to 50° C (+25° C Ref) 7ppm for UHF, 10ppm for VHF.
- Frequency deviation: \pm 4.5 KHz.
- Code format: 8 Cap Codes POCSAG
- Transmission speed: 512, 1200 and 2400 bps.
- Alert Tone Loudness: 100dB @ 10 cm
- Weight Without Battery: 430 grams.
- Size: 182.3 (L) x 114 (W) x 99.7 (H) mm.

WaveWare Technologies, Inc. **1-800-373-1466** www.WirelessMessaging.com