



*"Your Source for Pagers"*



## Unication Elegant / Legend

### Features:

#### DISPLAY

4-Line / 2-Line Text Zooming  
Programmable Default Zooming  
20 Alphanumeric Characters  
EL Backlight and Brightness Sensor for Auto Backlight  
Time and Date Display (Format Programmable)

#### ALERT

Alert Tone Programmed by way of PPS or Front Panel  
Reminder Alert (Tone Selectable)  
Louder Alert SPL ( $\leq 80$ dB at 12 inch)  
7 Alert Modes Selectable (Standard Alert, Escalating Alert, Vibrating, Intermittent Vibrate, Vibrate and Alert, Vibrate and then Alert, Chirp and Silent)  
16 Audio Alerts and 2 Vibrating Alerts (Normal and Intermittent)  
Expanded Alert Options for Maildrop  
Assign a Different Alert for Each Cap Code

#### INDICATORS

Unread Messages, Out of Range, Battery, Memory Full, Alarm  
Clock, Private Time On, On/Off Duty, Alert Mode

#### Messaging

8 RIC (32 Sub-Addresses) 16 RIC (64 Sub-Addresses)  
On / Off Duty Receiving Mode  
Total 32 KB Message Memory Capacity  
Duplicate Message Detection  
Important Messages Lock  
Notebook Entries  
Message Review, Time and Date Stamping, Alarm  
Auto On / OFF  
Up to 2025 Characters for 1 Personal Message  
Up to 5052 Characters for 1 Maildrop Message

### Specifications:

- **Frequency Range** (Wide or Narrow Band)  
UHF=450-470MHz  
VHF=137-174MHz  
900=929-932MHz
- **Baud Rate**  
512, 1200, 2400
- **Code Format**  
POCSAG (CIR No. 1 NRZ FSK)
- **Paging Sensitivity**  
Baud 512:  $\leq 5.7$   
Baud 1200:  $\leq 8$   
Baud 2400:  $\leq 10.3$
- **Channel Spacing**  
WB= 25 KHz NB= 12.5 KHz
- **Receiver Type**  
Synthesized
- **Address Capability**  
Elegant: 8 RIC (32 Sub Addresses)  
Legend: 16 RIC (64 Sub Addresses)
- **Frequency Deviation**  
WB=  $\pm 4.5$  KHz  
NB=  $\pm 2.25$  KHz
- **Alert Tone SPL**  
> 80dB @ 12 in (2370 Hz Standard Alert)
- **Power Supply**  
Single AA Alkaline Battery, 1.5v
- **Low Battery Alert**  
1.24 volts (Programmable)
- **Weight with Battery**  
87.5 g (3.1 oz.)
- **Dimensions**  
3.19"W x 2.16"H x 0.73"D

WaveWare Technologies, Inc. Sales: 1-800-373-1466 Fax: 972.479.1735

[www.WirelessMessaging.com](http://www.WirelessMessaging.com)