

Unication Elegant Alphanumeric Pager



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com

NOTE: Frequency Required when Ordered



P/N= 0901-0012 for UHF (460-470)

P/N= 0901-0011 for UHF (450-460)

P/N= 0901-0010 for VHF (100 MHz)

P/N= 0901-0013 for (929-932 MHz)

Features:

- 4-Line with 2-Line Zoom
- Intrinsically Safe
- Programmable Default Zoom
- 20 Alphanumeric Characters
- EL Backlight and Brightness Sensor for Auto Backlight
- Time and Date Display (Format Programmable)
- Alert Tone Programmed by PC Software or by Front Panel
- Pager Programming: PC Software Only (Sold Separately)
- Reminder Alert: Tone Selectable
- 7 Alert Modes (Selectable): Standard Alert, Escalating Alert, Vibrating, Intermittent Vibrate, Vibrate / Alert, Vibrate and then Alert and Chirp and Silent
- 16 Audio Alerts and 2 Vibrating Alerts
- Assign a Different Alert for each Cap Code
- Indicators: Unread Message, Out of Range, Battery, Memory Full, Alarm Clock, Private Time ON, ON / OFF Duty, Alert Mode
- Memory: 32 KB Capacity
- Duplicate Message Detection
- Message Lock / Message Review / Time and Date Stamping
- Auto ON / OFF
- ON / OFF Receiving Mode
- Personal Message: Up to 2025 Characters for 1 Message
- Mail Drop Message: Up to 5052 Characters for 1 Mail Drop

Specifications:

- Model: Elegant / Legend
- Frequency: 450-470 MHz, 137-174 MHz and 929-932 MHz
- Paging Sensitivity: 512bps \leq 5.7, 1200bps \leq 8 and 2400bps \leq 10.3
- Pager Baud Rate: 512 / 1200 / 2400bps for POCSAG
- Channel Spacing: 25 KHz (WB)
- Code Format: POCSAG
- Receiver Type: Synthesized
- Alert Tone Loudness: 80db @ 12 inches
- Cap Codes: 8 Cap Codes for POCSAG and 16 Cap Codes for FLEX
- Frequency Deviation: \pm 2.25 for Narrow Band
- Power Supply: 1 "AA" Alkaline Battery
- Low Battery Alert: 1.24 volts (Programmable)
- Weight with Battery: 87.5 grams
- Dimensions: 3.16 (W) x 2.16 (H) x 0.73 (D) inches