

Unication NP-30 Numeric Pager



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com



P/N= NP-30 For UHF and VHF

NOTE: Frequency Required when Ordered

Features:

- Large Display
- Back-Light
- Date and Time Display
- Pager Programming: PC Software Only (Sold Separately)
- Reminder Alert: Tone Selectable
- Alert Modes: Tone, Vibration, Melody and Silent
- Memory Backup (when Replacing Battery)
- Message Full Indicator
- Out of Range Indicator
- Low Battery Alert and Indicator
- Memory Capacity: 16 Messages Total of 320 Digits
- Delete Messages: All Messages or One Message
- Message Time Stamping

Specifications:

- Model: NP-30
- Frequency: 450-470 MHz and 143-174 MHz
- Paging Sensitivity: 512bps \leq 5.7 , 1200bps \leq 8 and 2400bps \leq 10.3
- Pager Baud Rate: 512 / 1200 / 2400bps for POCSAG
- Channel Spacing: 25 KHz (WB)
- Code Format: POCSAG
- Receiver Type: Synthesized
- Alert Tone Loudness: 75db @ 12 inches
- Cap Codes: 6 Cap Codes for POCSAG
- Spurious Rejection: > 40db
- Image Rejection: > 40db
- Inter-modulation Rejection: > 50db
- Intermediate Frequency: 21.4 MHz / 455 KHz
- Power Supply: 1 "AA" Alkaline Battery
- Dimensions: 2.0 (W) x 2.7 (H) x 0.7 (D) inches