

TE- 210AD Paging System



"We Deliver Information at the Speed of Light"



Key Specifications and Features:

- POCSSAG Transmitter
- Desktop Model
- Friendly User Interface
- 15 Buttons
- Available to set Frequency, Cap code and send message by External Keyboard
- Available to Connect to PABX
- Active Voltage Range is 8.4 VDC
- Keyboard (PS2 Input)
- Backlit LCD Screen, 4-Lines, Total 84 Alphanumeric on Display
- Support for Comp1, Comp2, Scope, GAComp2, TAP Protocols
- Range of ½ mile plus with Basic Antenna Shown
- RS- 232 Port for Programming and Serial Data
- Alarm Input 7 Pins: Dry Contact, 0 and 5V Low Active
- Range Test; Alarm Message Edit; Alarm Status Check; Clock Setup
- Optional Amplifier Add-On for 5 watt output

Specifications:

Model:

TE210AD Desk Top Transmitter

Frequency:

VHF 147- 170MHz, UHF 450- 470MHz

Modulation Type:

FSK

Channel Spacing:

12.5KHz / 25KHz

Output Power:

1 Watt

Maximum Deviation:

± 4.5KHz

Harmonic Radiation:

Less – 25dbm

Frequency Stability:

2.5 ppm at -10° C ~ 60°

Output Connect:

BNC (F)

Current Consumption:

Stand by: 100mA; Transmit: 400mA

Dimension:

232 (L) x 170 (W) x 50 (H) mm (without antenna)

Weight:

Approximately 650g (without antenna)