

TE- 210ADV Paging System



"We Deliver Information at the Speed of Light"



Key Specifications and Features:

- POCSSAG & 2-Tone Voice Transmitter
- Desktop Model
- Friendly User Interface
- 15 Buttons
- Available to set Frequency, Cap code and send message by External Keyboard
- Available to Connect to PABX
- Active Voltage Range is 8.4 VDC
- Mini- Keyboard (PS2 Keyboard Input Option)
- Backlit LCD Screen, 4-Lines, Total 84 Alphanumeric on Display
- Support for Comp1, Comp2, Scope, GAComp2, TAP Protocols
- Range of ½ mile plus with Basic Antenna Shown
- RS- 232 Port for Programming and Serial Data
- Alarm Input 7 Pins: Dry Contact, 0 and 5V Low Active
- Last Message
- Search Pager
- 99 Pre-Programmed Messages
- Range Test; Alarm Message Edit; Alarm Status Check; Clock Setup
- Can Select Baud Rate, Cap code, Alpha, Tone Only, Function Code and Group Code for each Number

Specifications:

Model:
TE300 Desk Top Transmitter

Frequency:
VHF 147- 170MHz, UHF 450- 470MHz

Modulation Type:
FSK

Channel Spacing:
12.5KHz / 25KHz

Output Power:
1 Watt

Maximum Deviation:
± 4.5KHz

Harmonic Radiation:
Less – 25dbm

Frequency Stability:
2.5 ppm at -10° C ~ 60°

Output Connect:
BNC (F)

Current Consumption:
Stand by: 100mA; Transmit: 400mA

Dimension:
232 (L) x 170 (W) x 50 (H) mm (without antenna)

Weight:
Approximately 650g (without antenna)