

Apollo **TE-210 BN** Paging System



“We Deliver Information at the Speed of Light”

Key Features / Specifications:

- Pocsag Transmitter
- Desk Type
- User friendly interface
- 15 Buttons

Features:

- Active Voltage Range: DC 8.4V
- Output power up to 1 watt
- Backlit super twist LCD screen, 4 Lines
- RS232 port for serial data and programming
- Can select baud rate, cap code, alpha, tone only, function code, and group code for each number
- Last message
- Search pager
- Range test
- Clock setup



**TE210BN Transmitter
Hospitality Paging System**

Specifications:

- **Model:**
TE210BN Desk Type Transmitter
- **Frequency range TX:**
VHF 147~170MHz, UHF 450~470MHz
- **Modulation Type:**
FSK
- **Channel Spacing:**
12.5KHz
- **Output Power:**
1W
- **Maximum Deviation:**
2.5KHz
- **Harmonic Radiation:**
less - 25dBm
- **Frequency Stability:**
2.5 ppm at -10C~60C
- **Output Connect:**
BNC (F)
- **Current Consumption:**
Standby: 120mA; Transmit: 420mA
- **Dimension:**
150 (W) x 42.6 (H) x 201.5 (D) mm (Without Antenna)
- **Weight:**
Approximately 770 g (Without Antenna)