



## **“Your Source for Paging Systems”**

### **PT-5000-KW - 19” Rack Mount High Power Paging Terminal**



#### **Specifications:**

- **Paging Encoding:**

WaveWare SPS-5 v8 or SPS-5 v9 Encoder Board, built-in.

- **Transmitter:**

Kenwood Base Station/Repeater Models Include: TKR-850 UHF or TKR-750 VHF.

- **Band Width:**

Narrow Band (12.5 kHz).

- **Paging Protocols:**

POCSAG Alphanumeric, Numeric, Tone/Vibe at RF Data Rates of 512, 1200 and 2400 bps Auto-switching.

- **Serial Interface Protocols:**

TAP v1.8, Comp1, Comp2, Scope and WaveWare.

- **Frequency Programming:**

Frequency(s) are factory programmed and can be set up with multiple channels and with different power levels.

**NOTES:**

-For continuous “High Traffic” paging needs at **25 watts** or Less.

-Requires an **External Antenna**.

- **Power Supply:**

Model SEC-1223-R1

13.8 VDC output, 120 VAC input

Rated at 23 Amps

- **RF Power Out:**

5-50 watts VHF or 5-40 watts UHF.

- **Pager Database:** 5,000 Maximum, EEPROM

Programmed with Windows based programming software, (included with each system).

- **Compatible with:**

-WaveWare Enterprise Messaging Software

-WaveWare Alert Utility Software

-WaveWare Call Manager Software

- Emergin / Philips Systems

-And Variety of other Nurse Call Systems

- **Dimensions:**

Approximately: 19” W x 15” D x 9” H

**WaveWare Technologies, Inc.**

**1.800.373.1466**

**[www.WirelessMessaging.com](http://www.WirelessMessaging.com)**

**“We Deliver Information at the Speed of Light”**