

Electro-Matic LED Displays

LED Clock



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= FVD44S1RX
P/N= FVD44S1RXP

Features:

- 4-Digit Numeric LED Display
- Up-Down Counter
- Up-Down Timer - Will Count Up or Down in 2 Modes: Hours and Minutes or Minutes and Seconds
- 12 Hour with AM / PM Indicators or 24 Hour Military Time
- 2-Levels of Brightness – Normal or High Bright Dip Switch Selectable
- Automatic Daylight Savings Time Adjustment Capable
- Side Access Buttons for Time / Master / Slave Adjustments
- Time Zone Functionality – Dip Switch Selectable
- Dry Contact Inputs - for Up / Down Counting or Increment / Decrement Functions
- Alarm Outputs - Capable of Driving 5 Amp Alarm Device with 19 Programmable Set Points
- Communications – RS-485 or Push Button Input
- Network Capable – RS-485 Port: Set Dip Switches for the IP Addresses on the Display to Network the Displays over Long Distances

Specifications:

- Model: **FVD44S1RX** (Non-Pre-Wired Connector)
- Model: **FVD44S1RXP** (Pre-Wired Connector)
- Case: Lightweight Aluminum with Plastic End Caps
- LED Color: High Bright Red
- Pixel Pitch: 0.3"
- Characters: 4" Tall (One-Line)
- Pixel Pitch: 0.3"
- Viewing Angle: 150 Degrees Minimum
- Temp Rating: -20 Degrees C to +70 Degrees C
- Dimensions: Case – 13.1" W x 6.2" H x 2" D
- Weight: Approx – 1.1 Lbs.
- Power: 120v AC
- Backup Power: Built-in Power Backup for Short Power Loss Durations