

ASCII Table

HEX	Character	Description	HEX	Character	HEX	Character	HEX	Character
0	NUL	Null	20	Space	40	@	60	`
1	SOH	Start of Heading	21	!	41	A	61	a
2	STX	Start of Text	22	“	42	B	62	b
3	ETX	End of Text	23	#	43	C	63	c
4	EOT	End of Transmission	24	\$	44	D	64	d
5	ENQ	Enquiry	25	%	45	E	65	e
6	ACK	Acknowledge	26	&	46	F	66	f
7	BEL	Bell	27	'	47	G	67	g
8	BS	Backspace	28	(48	H	68	h
9	TAB	Horizontal Tab	29)	49	I	69	i
A	LF	NL Line Feed, New Line	2A	*	4A	J	6A	j
B	VT	Vertical Tab	2B	+	4B	K	6B	k
C	FF	NP Form Feed, New Page	2C	,	4C	L	6C	l
D	CR	Carriage Return	2D	-	4D	M	6D	m
E	SO	Shift Out	2E	.	4E	N	6E	n
F	SI	Shift In	2F	/	4F	O	6F	o
10	DLE	Data Link Escape	30	0	50	P	70	p
11	DC1	Device Control 1	31	1	51	Q	71	q
12	DC2	Device Control 2	32	2	52	R	72	r
13	DC3	Device Control 3	33	3	53	S	73	s
14	DC4	Device Control 4	34	4	54	T	74	t
15	NAK	Negative Acknowledge	35	5	55	U	75	u
16	SYN	Synchronous Idle	36	6	56	V	76	v
17	ETB	End of Trans. Block	37	7	57	W	77	w
18	CAN	Cancel	38	8	58	X	78	x
19	EM	End of Medium	39	9	59	Y	79	y
1A	SUB	Substitute	3A	:	5A	Z	7A	z
1B	ESC	Escape	3B	;	5B	[7B	{
1C	FS	File Separator	3C	<	5C	\	7C	
1D	GS	Group Separator	3D	=	5D]	7D	}
1E	RS	Record Separator	3E	>	5E	^	7E	~
1F	US	Unit Separator	3F	?	5F	_	7F	DEL