

ALPHANUMERIC PAGER AP700



Our TFT screen provides clearer contrast due to its superior active matrix display technology. To add, it is a compact display with lower energy needs - allowing batteries to last much longer than older versions of LCD screens. This easy-to-replace screen option provides a more convenient screen repair option - generating shorter turnaround times for necessary screen repairs.

Product Description

- Up to 8 capcodes capability for POCSAG
- 4 keys operation, user friendly interface
- 4 lines, total of 84 Alphanumeric one page display
- Large memory size; total capacity 28,672 letters for POCSAG
- 16 memory slots, 10 sets full message
- 4 beep alerts, 10 melody alerts, vibration sleep mode
- 5 daily alarm sets



WaveWare Technologies, Inc.

2630 National Dr.
Garland, TX 75041

1-800-373-1466

www.wirelessmessaging.com

| | |
|----------------------------|---|
| SKU | 700 |
| FREQUENCY | UHF 430~470 MHz, VHF 135~174 MHz |
| PAGING SENSITIVITY | 1200bps-7 μ V/M, 2400bps-9 μ V/M, 512-5 μ V/M |
| BIT RATE | 512 / 1200 / 2400bps for POCSAG |
| CHANNEL SPACING | 12.5KHz, 25KHz |
| CODE FORMAT | POCSAG |
| SPURIOUS REJECTION | 40dB below carrier |
| ALERT TONE LOUDNESS | 87db @ 10 cm |
| CAPCODES | 8 Capcodes for POCSAG |
| BATTERY | AAA Alkaline batteries |
| DIMENSION | 2.9(L) x 2(W) x .75(H) in |
| WEIGHT | 1.75 oz |