

# WaveWare WT 802 Alphanumeric Pager

Powered By Daviscomms



**WaveWare Technologies, Inc.**

“Enhancing Mobile Alert Response”

Visit Our Website at:

[www.WirelessMessaging.com](http://www.WirelessMessaging.com)

2630 National Dr. Garland TX. 75041 PH: 1.800.373.1466



Part Number = **WT-802**

## Features:

- POCSAG Paging Format
- 4-Line Alphanumeric Display (20 Characters Per Line)
- Zoom 4-Line to 2-Line
- EL Back Light
- Battery Level Indicator
- Low Cell Reminder
- Time and Date Display
- Time and Date Stamping
- Priority Call
- Out of Range Indicator
- Adjustable LCD Contrast (0-7 Levels)
- 1 Daily Alarm
- Unread Message Reminder
- Encrypted Messaging via WaveWare SNAP

Plus:

- 4 Selectable Alert Durations (Programming Software)
- 3 Selectable Alert Modes (Programming Software)
- Tone Message (Programming Software)

## Additional Features:

- **Cap Code:** Up to 7 Cap Codes
- **Baud Rate:** 512, 1200 & 2400
- **Frequency Bands:** UHF 450-470 MHz  
(One Band for 450 to 470MHz) Stock Pager
- **VHF = 135-175 MHz**  
(Band Splits Coming Soon) Non-Stock, Special Order
- **Programming:**  
1: By Hand (Button Programming)  
2: By Pager Cradle and Windows Software  
Kit is **PN= PGRM-WT** (Purchased Separately)
- **Pager Includes:**  
- Holster with Belt Clip
- **Plus, Much More**

## Specifications:

- **Display:** Large TFT Color Display, 2.2 Inch, 320x240 Pixels
- **Operating Temperature:** -10 C to +50 C
- **Storage Temperature:** -40 C to +85 C
- **Alert Tone Loudness:** 75 dB @ 12 Inches
- **Weight:** 65 grams
- **Battery Type:** One Alkaline AA
- **Battery Life:** Dependent on Usage
- **Dimensions:** 80 x 54 x 19 mm

## Additional Specifications:

	UHF / VHF
Channel Spacing:	25KHz, 12.5KHz
Paging Sensitivity:	-104 dBm
EIA Selectivity:	50 dB
EIA Spurious and Image Rejection:	50 dB
IM Rejection:	50 dB