

Sounder-Strobe Combo

For Annunciation when used with LED Signs, Wall Pagers and other Relay Triggered Devices



"Enhancing Mobile Alert Response"

Visit Our Website at:

www.WirelessMessaging.com



PN= 0601-0118
Surface Mount



PN= 0601-0100
Wall Mount

Features:

- Multi-Tone Sounder in Combination with Xenon Flash
- Optical and Audible Signal can be Triggered Separately
- Choice of 8 Different Tones
- Adjustable Sound Output Level
- High Protection Rating IP 65
- Ready to Attach to WaveWare AS-Series LED Sign if you have the Relay Cable Harness, Sold Separate
- Easy to Mount

Specifications:

- Model: 0601-0100, Wall Mount Sounder / Strobe Kit
- Model: 0601-0118, Surface Mount Sounder / Strobe Kit
- Dome: Red
- Connection: Molex Connector for use with AS-Series Sign / Wall Pager Relay Cable
- Voltage: 24 Volts DC
Comes Wired and Ready with AC to DC Adaptor
- Flash Frequency: 1 Hz
- Sound Output: 100 dB
- Mounting: Surface, Mounting Holes in Rim of Enclosure
- Dimensions: 89mm Dia. X 105mm H



Mount on Sign



Mount on Wall

Tone Types and Frequencies:

- Tone #1: Horn Tone
- Tone #2: Continuous Tone (ca. 2.3 KHz)
- Tone #3: 1 Hz Tone (c. 2.3 KHz)
- Tone #4: 20 Hz Whistle Tone (ca. 2.3 KHz)
- Tone #5: 800-970 Hz Rising @ 1 Hz
- Tone #6: 2400-2850 Hz Rising @ 7 Hz
- Tone #7: 1200-500 Hz Falling @ 1 Hz
- Tone #8: Alternating Tone 800 Hz to 1200 Hz @ 1 Hz