Apollo VP-101 Pager

2-Tone Voice Series



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com



P/N= VP101

Heavy Duty, Rugged Case and Strong Belt-Clip

Key Features:

- IP52 Approved
- Single Channel (Frequency)
- Tone and Vibrate Alert / Loud Clear Alert Level
- Large Volume Control Knob
- Slide Switch: On / Off with Vibrate or Alert Selection
- Rechargeable: One "AA" Ni-MH Battery (Included)
- "AA" Alkaline Battery Acceptable
- 6 Calls: 4 Individual and 2 Group Call
- Voice Storage Option: 120 Sec Memory:
 1- 4 Stored Voice Slots @ 30 Seconds each
- Priority Alert Programmable
- Monitor Channel Function / Monitor with Carrier Squelch
- Fixed Alert Volume (Programmable)
- Programmed by PC Software
- External Earphone Jack
- Reminder Tone and LED Reminder Flash
- 2 Status LED Indicators:
 Red LED Flashed for Alert, Lit for Unread Voice Message.
 Green Blinking LED when Monitor ON
 Green Solid LED when Audio Lock ON
- Desktop Charging Base (Included)

NOTE: Frequency Required when Ordered

Specifications:

Model: VP-101

• Frequency: 406-500 MHz and 138-174 MHz

Paging Sensitivity: 5 µV/M

• 12DB SIAND Sensitivity: 12 μV/M

Channel Spacing: 25 KHz (WB) or 12.5KHz (NB)

Code Format: 2-Tone Sequential Decoding

Adjacent Channel Selectivity: 55 db

Spurious and Image Rejection: 55db below carrier

Alert Tone Loudness: 90dba @ 30 cm

Voice Loudness: 87dba @ 30 cm

Power Consumption: 8.2mA (without Power Save)

Battery Life: Approx. 20 Days (10 days without Power Save)
 Based on 8 Hrs per day and 5 Messages at 30 Sec Each

Weight: Approx. 177 Grams w/ Battery

Dimension: 80 (L) x 53 (W) x 24.5 (H) mm



VP-101 Desktop Charging Base

WaveWare Technologies, Inc. 1.800.373.1466 <u>Sales@WirelessMessaging.com</u> 3.14.2012