Apollo VP-200 Pager

2-Tone Voice Series



"Your Source for Pagers"

Visit Our Website at:

www.WirelessMessaging.com

NOTE: Frequencies Required when Ordered

Key Features:

- IP54 Approved (Protection from Rain / Dust)
- Option: Single or Dual Channel (Frequency)
- Synthesized
- Programmable Tone and Vibrate Alerts
- User Programmable Tones for Different Addresses
- Large 4 Position Selector Knobs
- Function Mode Announcement
- Priority Scan, Normal Scan and Silent Scan Functions
- Rechargeable: One "AA" Ni-MH Battery (Included)
- 12 Calls: 8 Individual Calls and 4 Group Calls
- Voice Storage Option: 8 Minutes Total Memory:
- Priority Alert Programmable
- Channel Monitor Function
- Low Battery Alert
- Earphone Jack
- Programmed by PC Software
- Standard Desktop Charging Base (Included)
- Optional Amplified Charging Base: Quick Charging (Full Charge in Approx. 2 Hours) Built-in External Speaker / Audio Amplifier Amplifier Relay Feature Optional External Antenna Available Weight: 402.50 Grams Size: 170 (L) x 123.50 (W) x 55 (H) mm



P/N= VP200

Heavy Duty, Rugged Case and Strong Belt-Clip

Specifications:

- Model: VP-200
- Frequency: 406-512 MHz, 143-147 MHz, 33-49 and 84-88 MHz
- Paging Sensitivity: 5 μV/M / Sensitivity Alerting: 4 μV/M
- Selectivity: 60 db / Frequency Stability: 10ppm
- Channel Spacing: 25 KHz (WB) or 12.5KHz (NB)
- Code Format: 2-Tone Sequential Decoding
- Maximum Frequency Separation: : 8 MHz
- Spurious and Image Rejection: 55db below carrier
- Audio Output @ 12: 95 / 93dba (Audio / Voice)
- Voice Level: 93dba @ 12
- Power Consumption: 8.2mA (without Power Save)
- Battery Life: Approx. 10 Days Based on 8 Hrs per day and 6 Messages at 30 Sec Each
- Weight: Approx. 177 Grams w/ Battery
- Dimension: 80 (L) x 53 (W) x 24.5 (H) mm



Standard Base Amplified Base VP-200 Charging Bases

WaveWare Technologies, Inc. 1.800.373.1466 <u>Sales@WirelessMessaging.com</u> 3.14.2012