

Apollo TE-310 Paging System

Hospitality Paging System



"We Deliver Information at the Speed of Light"

Visit Our Website at:

www.WirelessMessaging.com



P/N= 0119-1000

NOTE: Frequency Required when Ordered

Key Features:

- POCsAG Transmitter
- Stand Alone / Ideal for Communications Between the Kitchen and Waiters or other Staff Members
- User Friendly Interface
- 16 Buttons / LED Lit when Active
- RS-232 Port: For PC Programming Only
- Pagers: Works w / Coaster, Paddle, E-Pager and Numeric
- Option: 5-watt Output - UHF RF Booster (TA-500)
P/N= 0119-1002

Overview:

Press any Button to Activate and that Button's LED will Light up and Send a Page Assigned to that Button Number.

Button Numbers 1- 16 can be Marked easily with Assigned Name for that Pager Number.

Button LED will Stay Lit and Continue to Send a Page until the Button is Pressed again.

De-Activate (Stop Sending Page) by Pressing the Pager Number again. The LED will Turn OFF and the Page will Stop for that Pager Number.

Specifications:

- Model: TE-310 Designed for Kitchen Call Applications
- Paging Format: POCsAG
- Frequency: UHF 450-470 MHz and VHF 147-170 MHz
- Modulation Type: FSK
- Channel Spacing: 12.5 Narrow Band (NB)
- RF Output Power : 1 watt (5 watt Booster Available)
- Input Voltage: 8.4 v DC
- Current Consumption: Standby 100mA and TX 400mA
- Harmonic Radiation: Below -25 dbm
- Frequency Stability: 2.5 ppm at -10° C to 60° C
- Output Connect: BNC (F)
- Power LED: Lit when system is Turned ON (Orange)
- Transmit LED: Lit when Transmitting a Page (Green)
- Weight: Approximately 770g (w/o Antenna)